



**SIDDHARTH INSTITUTE OF ENGINEERING & TECHNOLOGY
(AUTONOMOUS):: PUTTUR**

Siddharth Nagar, Narayanavanam Road – 517583

QUESTION BANK (DESCRIPTIVE)

Subject with Code : Theory of Machines (19ME0310)

Course & Branch : B.Tech – ME

Year & Sem: II-B. Tech & II-Sem

Regulation: R19

UNIT-I (PRECESSION & TURNING MOMENT DIAGRAM)

1	The propeller of aero weighs 550 N and has radius of gyration of 0.9m. The propeller shaft rotates at 1900 r.p.m, clockwise, as viewed from tail end. The plane turns left, making a U turns, i.e., through 180° of 125m radius, at a speed of 330 km/hr. Determine the gyroscopic couple and its effect on the aircraft. Also find the reaction on bearings if the distance between two bearings of the propeller is 0.8m.	L5	12 M
2	A ship is pitching through a total angle of 15° , the oscillation may be taken as simple harmonic and the complete period is 32 seconds. The turbine rotor weighs 6 tons, its radius of gyration is 45cm and it is rotating at 2400 r.p.m. Calculate the maximum value of gyroscopic couple set up by the rotor and its effect, when the bow is descending and the rotor is rotating clockwise looking from aft. What is the maximum angular acceleration to which the ship is subjected to while pitching ?	L1	12 M
3	The turbine rotor of a ship has 2.4 tonnes and rotates at 1750 r.p.m clockwise when viewed from the aft. The radius of gyration of the rotor is 300 mm. Determine the gyroscopic couple and its effect when <ol style="list-style-type: none"> The ship turns right at an radius of 250 m with a speed of 22 kmph, The ship pitches with the bow rising at an angular velocity of 0.85 rad/sec, and The ship rolls at an angular velocity of 0.15 rad/sec. 	L5	12 M
4	A racing car weighs 20 KN. It has a wheel base of 2 m, track width 1 m and height of C.G. 300mm above the ground level and lies midway between the front and rear axle. The engine flywheel rotates at 300 r.p.m clockwise when viewed from the front. The moment of inertia of the flywheel is 4 kg-m^2 . Find the reactions between the wheels and the ground when the car takes a curve of 15 m radius towards right at 30 km/hr, taking into consideration the gyroscopic and the centrifugal effects. Each wheel radius towards radius is 400 mm.	L1	12 M
5	Each road wheel of a motor cycle has a mass moment of inertia of 1.5 kg-m^2 . The rotating parts of the engine of the motor cycle have a mass moment of inertia of 0.25 kg-m^2 . The speed of the engine is 5 times the speed of the wheels and is in the same sense. The mass of the motor cycle with its rider is 250kg and its centre of gravity is 0.6 m above the ground level. Find the angle of heel if the cycle is traveling at 50 km/hr	L1	12 M

	and is taking a turn of 30 m radius. The wheel diameter is 0.6 m.		
6	(a) A vertical double steam engine develops 75 KN at 250 r.p.m. the maximum fluctuation of energy is 30 percent of the work done per stroke. The maximum and minimum speeds are not to vary more than 1% on either of the mean speed. Find the mass of the fly wheel required if the radius of gyration is 0.6 meters.	L1	6M
	(b) The radius of gyration of a fly wheel is 1 meter and the fluctuation of speed is not to exceed 1% of the mean speed of the fly wheel. If the mass of the fly wheel is 3340 kg and the steam engine develops 150 KW at 135 r.p.m. then find 1) Maximum fluctuation of energy, and 2) Coefficient of fluctuation of energy.	L1	6 M
7	The turning moment diagram for a petrol engine is drawn to a vertical scale of 1mm to 6 Nm and horizontal scale of 1mm to 10. The turning moment repeats itself after every half revolution of the engine. the areas above and below the mean torque line are 305, 710, 50, 350, 980, and 275mm ² . Mass of rotating parts is 40 kg at a radius of gyration of 140 mm. Calculate the coefficient of fluctuation of speed if the mean speed is 1500 r.p.m.	L1	12 M
8	The turning moment diagram for a multi-cylinder engine has been drawn to scale of 1mm =4500N-m vertically and 1mm=2.4 0 horizontally. the intercepted areas between output torque curve and mean resistance line taken in order from one end are 342, 23, 245, 303, 115, 232, 227 and 164 mm ² , when the engine is running at 150 r.p.m. if the mass of the fly wheel is 1000 kg and the total fluctuation of speed does not exceed 3% of mean speed, find the minimum value of the radius of gyration.	L1	12 M
9	The torque delivered by a two-stroke engine is represented by $T=100+300 \sin^2(\theta)-500\cos^2(\theta)$ N-m, Where 'θ' is the angle turned by the crank from the inner-dead centre. The engine speed is 250 rpm. The mass of the flywheel is 400 kg and radius of gyration 400 mm. Determine: (i) the power developed , (ii) the total percentage fluctuation of speed, (iii) the angular acceleration of fly wheel when the crank has rotated through an angle of 60° from the inner dead centre, and (iv) the maximum angular acceleration and retardation of the fly wheel.	L4	12 M
10	The torque exerted on the crank shaft of a two-stroke engine is given by the equation (N-M) =145,00+2300sin ² (θ)-1900cos ² (θ) where 'θ' is the crank angle angle displacement from the inner dead centre. Assuming the resisting torque to be constant, determine ; 1. The power of the engine when the speed is 150 r.p.m. 2. The moment of inertia of the fly wheel if the speed variation is not to exceed ±0.5% of the mean speed, and 3. The angular acceleration of the fly wheel when the crank has turned through 300 from the IDC.	L5	12 M

UNIT –II (CLUTCHES, BRAKES AND DYNAMOMETERS)

1	(a) Explain the working of a single-plate clutch with neat sketch	L2	6M
	(b) A single plate clutch, effective on both sides, is required to transmit 25 kW at 3000 r.p.m. Determine the outer and inner radii of a frictional surface if the coefficient of friction is 0.255, the ratio of radii is 1.25 and the maximum pressure is not to exceed 0.1 N/mm ² . Also determine the axial thrust to be provided by springs. Assume the theory of uniform wear.	L5	6M
2	A multi-disc clutch has three discs on the driving shaft and two on the driven shaft. The outside diameter of the contact surfaces is 240 mm and inside diameter 120 mm. Assuming uniform wear and coefficient of friction as 0.3, find the maximum axial intensity of pressure between the discs for transmitting 25 kW at 1575 r.p.m.	L1	12M
3	An engine developing 45 kW at 1000 r.p.m. is fitted with a cone clutch built inside the flywheel. The cone has a face angle of 12.5° and a maximum mean diameter of 500 mm. The coefficient of friction is 0.2. The normal pressure on the clutch face is not to exceed 0.1 N/mm ² . Determine 1.the axial spring force necessary to engage to clutch, and 2.the face width required.	L5	12M
4	A conical friction clutch is used to transmit 90 kW at 1500 r.p.m. The semi cone angle is 20° and the coefficient of friction is 0.2. If the mean diameter of the bearing surface is 375 mm and the intensity of normal pressure is not to exceed 0.25 N/mm ² , find the dimensions of the conical bearing surface and the axial load required.	L1	12M
5	A centrifugal clutch is to transmit 15 kW at 900 r.p.m. The shoes are four in number. The speed at which the engagement begins is 3/4th of the running speed. The inside radius of the pulley rim is 150 mm and the center of gravity of the shoe lies at 120 mm from the center of the spider. The shoes are lined with Ferrodo for which the coefficient of friction may be taken as 0.25. Determine 1. Mass of the shoes, and 2. Size of the shoes, if angle subtended by the shoes at the center of the spider is 60° and the pressure exerted on the shoes is 0.1 N/mm ² .	L5	12M
6	A band brake acts on the 3/4th of circumference of a drum of 450 mm diameter which is keyed to the shaft. The band brake provides a braking torque of 225 N-m. One end of the band is attached to a fulcrum pin of the lever and the other end to a pin 100 mm from the fulcrum. If the operating force is applied at 500 mm from the fulcrum and the coefficient of friction is 0.25, find the operating force when the drum rotates in the (a) anticlockwise direction, and (b) clockwise direction.	L1	12M
7	A band and block brake, having 14 blocks each of which subtends an angle of 15° at the centre, is applied to a drum of 1 m effective diameter. The drum and flywheel mounted on the same shaft has a mass of 2000 kg and a combined radius of gyration of 500 mm. The two ends of the band are attached to pins on opposite sides of the brake lever at distances of 30 mm and 120 mm from the fulcrum. If a force of 200 N is applied at a distance of 750 mm from the fulcrum, find: 1. maximum braking torque, 2. angular retardation of the drum,	L1	12M

	and 3. time taken by the system to come to rest from the rated speed of 360 r.p.m. The coefficient of friction between blocks and drum may be taken as 0.25.		
8	Describe the construction and operation of a (a) Prony brake and (b) rope brake absorption dynamometer with neat sketch.	L2	12M
9	Describe with sketches one form of torsion dynamometer and explain in detail the calculations involved in finding the power transmitted.	L2	12M
10	A torsion dynamometer is fitted to a propeller shaft of a marine engine. It is found that the shaft twists 2° in a length of 20 metres at 120 r.p.m. If the shaft is hollow with 400 mm external diameter and 300 mm internal diameter, find the power of the engine. Take modulus of rigidity for the shaft material as 80 GPa.	L1	12M

UNIT -III (GOVERNORS)

1	(a) Explain with neat sketch the working principle of centrifugal/porter governor	L2	6M
	(b) Calculate the vertical height of a Watt governor when it rotates at 60 r.p.m. Also find the change in vertical height when its speed increases to 61 r.p.m.	L1	6M
2	(a) Derive the expression for Porter governor	L3	6M
	(b) Derive the expression for Proell governor	L3	6M
3	A Porter governor has equal arms each 250 mm long and pivoted on the axis of rotation. Each ball has a mass of 5 kg and the mass of the central load on the sleeve is 25 kg. The radius of rotation of the ball is 150 mm when the governor begins to lift and 200 mm when the governor is at maximum speed. Find the minimum and maximum speeds and range of speed of the governor.	L1	12M
4	The arms of a Porter governor are each 250 mm long and pivoted on the governor axis. The mass of each ball is 5 kg and the mass of the central sleeve is 30 kg. The radius of rotation of the balls is 150 mm when the sleeve begins to rise and reaches a value of 200 mm for maximum speed. Determine the speed range of the governor. If the friction at the sleeve is equivalent of 20 N of load at the sleeve, determine how the speed range is modified.	L5	12M
5	In an engine governor of the Porter type, the upper and lower arms are 200 mm and 250 mm respectively and pivoted on the axis of rotation. The mass of the central load is 15 kg, the mass of each ball is 2 kg and friction of the sleeve together with the resistance of the operating gear is equal to a load of 25 N at the sleeve. If the limiting inclinations of the upper arms to the vertical are 30° and 40° , find, taking friction into account, range of speed of the governor.	L1	12M
6	A Porter governor has all four arms 250 mm long. The upper arms are attached on the axis of rotation and the lower arms are attached to the sleeve at a distance of 30 mm from the axis. The mass of each ball is 5 kg and the sleeve has a mass of 50 kg. The extreme radii of rotation are 150 mm and 200 mm. Determine the range of speed of the governor.	L5	12M
7	A Proell governor has equal arms of length 300 mm. The upper and lower ends of the arms are pivoted on the axis of the governor. The extension arms of the lower links are each 80 mm long and parallel to the axis when the radii of rotation of the balls are 150 mm and 200 mm. The mass of each ball is 10 kg and the mass of the central load is 100 kg. Determine the range of speed of the governor.	L5	12M
8	A governor of the Proell type has each arm 250 mm long. The pivots of the upper and lower arms are 25 mm from the axis. The central load acting on the sleeve has a mass of 25 kg and the each rotating ball has a mass of 3.2 kg. When the governor sleeve is in mid-position, the extension link of the lower arm is vertical and the radius of the path of rotation of the masses is 175 mm. The vertical height of the governor is 200 mm. If the governor speed is 160 r.p.m. when in mid-position, find : 1. length of the extension link; and 2. tension in the upper arm.	L1	12M
9	A Hartnell governor having a central sleeve spring and two right-angled bell crank levers moves between 290 r.p.m. and 310 r.p.m. for a sleeve lift of 15 mm. The sleeve arms and the ball arms are 80 mm and 120 mm respectively. The levers are pivoted at 120 mm from the governor axis and mass of each ball is 2.5 kg. The ball arms are parallel to the governor axis at the lowest equilibrium speed. Determine : 1. loads on the spring at the lowest and the highest equilibrium speeds, and 2. stiffness of the spring.	L5	12M
10	What is meant by Sensitiveness of governors, Differentiate between a Governor and a	L1	12M

flywheel. What is meant by isochronous condition in Governors?

UNIT –IV (BALANCING OF ROTATING AND RECIPROCATING MASSES)

1	Four masses m_1 , m_2 , m_3 , and m_4 are 200 kg, 300 kg, 240 kg and 260 kg respectively. The corresponding radii of rotation are 0.2 m, 0.15 m, 0.25 m and 0.3 m respectively and the angles between successive masses are 45° , 75° and 135° . Find the position and magnitude of the balance mass required, if its radius of rotation is 0.2 m.	L1	12M															
2	A shaft carries four masses A, B, C and D of magnitude 200 kg, 300 kg, 400 kg and 200 kg respectively and revolving at radii 80 mm, 70 mm, 60 mm and 80 mm in planes measured from A at 300 mm, 400 mm and 700 mm. The angles between the cranks measured anticlockwise are A to B 45° , B to C 70° and C to D 120° . The balancing masses are to be placed in planes X and Y. The distance between the planes A and X is 100 mm, between X and Y is 400 mm and between Y and D is 200 mm. If the balancing masses revolve at a radius of 100 mm, find their magnitudes and angular positions.	L1	12M															
3	Four masses A, B, C and D as shown below are to be completely balanced <table border="1" data-bbox="315 821 1239 926" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> </tr> </thead> <tbody> <tr> <td>Mass (kg)</td> <td>—</td> <td>30</td> <td>50</td> <td>40</td> </tr> <tr> <td>Radius (mm)</td> <td>180</td> <td>240</td> <td>120</td> <td>150</td> </tr> </tbody> </table> <p>The planes containing masses B and C are 300 mm apart. The angle between planes containing B and C is 90°. B and C make angles of 210° and 120° respectively with D in the same sense. Find</p> <ol style="list-style-type: none"> The magnitude and the angular position of mass A ; and The position of planes A and D. 		A	B	C	D	Mass (kg)	—	30	50	40	Radius (mm)	180	240	120	150	L1	12M
	A	B	C	D														
Mass (kg)	—	30	50	40														
Radius (mm)	180	240	120	150														
4	A, B, C and D are four masses carried by a rotating shaft at radii 100, 125, 200 and 150 mm respectively. The planes in which the masses revolve are spaced 600 mm apart and the mass of B, C and D are 10 kg, 5 kg, and 4 kg respectively. Find the required mass A and the relative angular settings of the four masses so that the shaft shall be in complete balance	L1	12M															
5	A shaft carries four masses in parallel planes A, B, C and D in this order along its length. The masses at B and C are 18 kg and 12.5 kg respectively, and each has an eccentricity of 60 mm. The masses at A and D have an eccentricity of 80 mm. The angle between the masses at B and C is 100° and that between the masses at B and A is 190° , both being measured in the same direction. The axial distance between the planes A and B is 100 mm and that between B and C is 200 mm. If the shaft is in complete dynamic balance, determine: 1. The magnitude of the masses at A and D ; 2. the distance between planes A and D ; and 3. the angular position of the mass at D.	L5	12M															
6	Differentiate 'static balancing' and 'dynamic balancing'. State the necessary conditions to achieve them.	L5	12M															
7	A single cylinder reciprocating engine has speed 240 r.p.m., stroke 300 mm, mass of reciprocating parts 50 kg, mass of revolving parts at 150 mm radius 37 kg. If two third of the reciprocating parts and all the revolving parts are to be balanced, find : 1. The balance mass required at a radius of 400 mm, and 2. The residual unbalanced force when the crank has rotated 60° from top dead centre.	L1	12M															
8	Derive the following expression of effects of partial balancing in two cylinder locomotive engine (i) Variation of attractive force (ii) Swaying couple (iii) Hammer blow	L2	12M															

9	The following data refer to two cylinder locomotive with cranks at 90° : Reciprocating mass per cylinder = 300 kg ; Crank radius = 0.3 m ; Driving wheel diameter = 1.8 m ; Distance between cylinder centre lines = 0.65 m ; Distance between the driving wheel central planes = 1.55 m. Determine : 1. the fraction of the reciprocating masses to be balanced, if the hammer blow is not to exceed 46 kN at 96.5 km/hr. ; 2. the variation in tractive effort ; and 3. the maximum swaying couple.	L5	12M
10	A, B, C and D are four masses carried by a rotating shaft at radii 120, 150, 200 and 180 mm respectively. The planes in which the masses revolve are spaced 600 mm apart and the mass of B, C and D are 15 kg, 10 kg, and 8 kg respectively. Find the required mass A and the relative angular settings of the four masses so that the shaft shall be in complete balance	L1	12M

UNIT -V (MECHANICAL VIBRATIONS)

1	Derive an expression for the natural frequency of the free longitudinal vibration by (i) Equilibrium method (ii) Energy method (iii) Rayleigh's method	L3	12M
2	A cantilever shaft 50 mm diameter and 300 mm long has a disc of mass 100 kg at its free end. The Young's modulus for the shaft material is 200 GN/m ² Determine the frequency of longitudinal and transverse vibrations of the shaft.	L5	12M
3	A shaft of length 0.75 m, supported freely at the ends, is carrying a body of mass 90 kg at 0.25 m from one end. Find the natural frequency of transverse vibration. Assume E = 200 GN/m ² and shaft diameter = 50 mm.	L1	12M
4	Derive the natural frequency of Free Transverse Vibrations by (i) Rayleighs method (ii) Dunkerleys method.	L3	12M
5	A shaft 50 mm diameter and 3 metres long is simply supported at the ends and carries three loads of 1000 N, 1500 N and 750 N at 1 m, 2 m and 2.5 m from the left support. The Young's modulus for shaft material is 200 GN/m ² Find the frequency of transverse vibration.	L1	12M
6	A vibrating system consists of a mass of 200 kg, a spring of stiffness 80 N/mm and a damper with damping coefficient of 800 N/m/s. Determine the frequency of vibration of the system.	L5	12M
7	The measurements on a mechanical vibrating system show that it has a mass of 8 kg and that the springs can be combined to give an equivalent spring of stiffness 5.4 N/mm. If the vibrating system have a dashpot attached which exerts a force of 40 N when the mass has a velocity of 1 m/s, find : 1. critical damping coefficient, 2. damping factor, 3. Logarithmic decrement, and 4. ratio of two consecutive amplitudes.	L1	12M
8	Derive the Natural Frequency of Free Torsional Vibrations	L3	12M
9	A shaft of 100 mm diameter and 1 metre long has one of its end fixed and the other end carries a disc of mass 500 kg at a radius of gyration of 450 mm. The modulus of rigidity for the shaft material is 80 GN/m ² . Determine the frequency of torsional vibrations.	L5	12M
10	A circular rod of length 1.0 m, supported freely at the ends, is carrying a body of mass 100 kg at 0.35 m from one end. Find the natural frequency of transverse vibration. Assume E = 220 GN/m ² and shaft diameter = 60 mm.	L1	12M

PREPARED BY V.KARTHIKEYAN